



# VC4000 CHARGER XL-200P

## FLEXIBLE CHARGING FOR MAXIMUM PERFORMANCE

The VC4000 is a rapid charger with the capability to charge Lithium Ion batteries in 4 hours or less. The charger supports the XL-200P portable and is independent from frequency or system operation. The VC4000 can be mounted in a vehicle or used as a desk charger.

### FEATURES

The flexible design of the VC4000 provides the versatility to meet different users' needs. The unit can charge the battery with or without the radio attached and can also accommodate a radio with the speaker mic and/or belt clip still attached.

The charger may be hard wired for permanent installation or powered using the optional DC cigarette lighter adapter for temporary in-vehicle installation. The VC4000 may also be used for desktop charging with the optional AC adapter.

The unit is turned off when the ignition is turned off, preventing vehicle battery drain. This function is dipswitch configurable.

### STANDARD FEATURES

The VC4000 includes the following features:

- Colored LEDs: Provide charging status
- Positive Latch: Ensures that the radio or battery pack is securely in place while it is in the charger
- Versatile Mounting Options: Enables the charger to easily fit different vehicle mounting requirements
- Automatic Restart: Constantly monitors the battery while it is in the charger and will start charging the battery as soon as it falls below 90% of capacity.
- Optimal Charging without Overcharging: Provides microprocessor-controlled charging for long battery life and maximum battery performance
- Protective Circuitry: Prevents damage to battery resulting from charging batteries that are not within the required temperature or voltage range
- Charging Efficiency: Communicates with the battery's internal fuel gauge for optimal charging efficiency
- Repeater Control: Has an enable/disable circuit for use with a vehicular repeater. The vehicular repeater is enabled when the radio is removed from the charger

## GENERAL SPECIFICATIONS

**Applications:** Charges Lithium Ion batteries for the XL-200P

**Dimensions (D x W x H):**

With Bracket:

3.125 x 5.125 x 5.437 in.  
(7.94 x 13.02 x 13.81 cm)

Without Bracket:

3.125 x 4.312 x 4.375 in.  
(7.94 x 10.95 x 11.11 cm)

**Weight:**

With Bracket: 13.0 oz (368g)

Without Bracket: 10.2 oz (289g)

**Source Voltage:** 11 to 16 VCC

**Charge Current:** 1.5A

**Construction:** Polycarbonate and ABS blend

**Color:** Black

**Operating Temperature:**

-22 to +140°F (-30 to +60°C)

**Charging Temperature:**

+32 to +122°F (0 to +50°C)

**Mounting:**

Cables, hardware, U-shaped bracket for mounting above or beneath dash, fuse, connector terminals for repeater control, and ignition sense

**Options:** Power Supply Kit that includes AC Adapter and Cigarette Lighter Adapter

## RoHS Compliant

### About Harris Corporation

Harris Corporation is a leading technology innovator that creates mission-critical solutions that connect, inform and protect the world. The company's advanced technology provides information and insight to customers operating in demanding environments from ocean to orbit and everywhere in between. Harris has approximately \$8 billion in annual revenue and supports customers in 125 countries through four customer-focused business segments: Communication Systems, Space and Intelligence Systems, Electronic Systems, and Critical Networks.

## ENVIRONMENTAL SPECIFICATIONS

STANDARD	PARAMETER	METHODS & PROCEDURES
MIL-STD-810G	Vibration	514.6 PI, CAT 4 & 24
	Shock	516.6 PI, IV, V, & VI
	Solar Radiation	505.5 PI
	Low Temperature	502.5 PI & II
	High Temperature	501.5 PI & II
	Temperature Shock	503.5 PI-C
	Humidity	507.5 PI & II
	Low Pressure	500.5 PI

## OPTION NUMBER

VC4000 for XL-200P

XL-CH4W

## REGULATORY SPECIFICATIONS

FCC Certification:

Meets FCC Part 15

Industry Canada:

ICES-003

Automotive Directive:

72/245/EEC – 95/54/EC

 10R-037621



Technical specifications are subject to change without notice. Product sales are subject to applicable U.S. export control laws.

FLORIDA | NEW YORK | VIRGINIA | BRAZIL | UNITED KINGDOM | UAE | SINGAPORE

Harris is a registered trademark of Harris Corporation.  
Trademarks and tradenames are the property of their respective companies.

© 2016 Harris Corporation 08/16 CS-PSPC ECR-8101

**HARRIS**® TECHNOLOGY TO CONNECT,  
INFORM AND PROTECT™