



VERSATILE CHARGING FOR INCREASED PRODUCTIVITY

FEATURES

The versatile design of the VC4000 provides the flexibility to meet different users' needs. The unit can charge the battery with or without the radio attached and can also accommodate a radio with the speaker mic still attached.

The charger may be hard wired for permanent installation or powered using the optional DC cigarette lighter adapter for temporary in-vehicle installation. The VC4000 may also be used for desktop charging with the optional AC adapter.

Depending on the dipswitch configuration, the unit is turned off when the ignition is turned off, preventing vehicle battery drain, or the unit is on at all times.

VC4000 CHARGER

XG-SERIES AND P-SERIES PORTABLES

The VC4000 is a rapid charger with the capability to charge Lithium Polymer and Lithium Ion batteries in 4 hours or less and Nickel Cadmium and Nickel Metal Hydride batteries in 1.5 hours or less. The charger supports the XG-75P, XG-25P, XG-15P, P7300, P5500, P5400, and P5300 portables and is independent from frequency or system operation. The VC4000 can be mounted in a vehicle or used as a desk charger.

STANDARD FEATURES

The VC4000 includes the following features:

- **Colored LEDs:** Provide charging status
- **Positive Latch:** Ensures that the radio or battery pack is securely in place while it is in the charger
- **Versatile Mounting Options:** Enables the charger to easily fit different vehicle mounting requirements
- **Automatic Restart:** Constantly monitors the battery while it is in the charger and will start charging the battery as soon as it falls below 50 to 75% of capacity
- **Optimal Charging without Overcharging:** Provides microprocessor-controlled charging for long battery life and maximum battery performance
- **Protective Circuitry:** Prevents damage to battery resulting from charging batteries that are not within the required temperature or voltage range
- **Dual Charge and Trickle Rates:** Allow charge and trickle rates to be adjusted through dipswitch configuration
- **Repeater Control:** Has an enable/disable circuit for use with a vehicular repeater. The vehicular repeater is enabled when the radio is removed from the charger

GENERAL SPECIFICATIONS

Applications: Charges Lithium Polymer, Lithium Ion, Nickel Metal Hydride, and Nickel Cadmium batteries

Dimensions (D x W x H):

With Bracket:
3.125 x 5.125 x 5.437 in.
(7.94 x 13.02 x 13.81 cm)
Without Bracket:
3.125 x 4.312 x 4.375 in.
(7.94 x 10.95 x 11.11 cm)

Weight:

With Bracket: 13.0 oz (368g)
Without Bracket: 10.2 oz (289g)

Source Voltage: 11 to 16 VDC

Charge Current: 1.5 or 0.75A
(switch selectable)

Trickle Rate: 200 or 100 mA
(switch selectable)

Construction: Polycarbonate and ABS blend

Color: Black

Operating Temperature:

-22 to +140°F (-30 to +60°C)

Charging Temperature:

+40 to +113°F (+5 to +45°C)

Mounting:

Cables, hardware, U-shaped bracket for mounting above or beneath dash, fuse, connector terminals for repeater control, and ignition sense

Options: Power Supply Kit with AC Adapter and Cigarette Lighter Adapter

RoHS Compliant

About Harris Corporation

Harris Corporation is a leading technology innovator that creates mission-critical solutions that connect, inform and protect the world. The company's advanced technology provides information and insight to customers operating in demanding environments from ocean to orbit and everywhere in between. Harris has approximately \$8 billion in annual revenue and supports customers in 125 countries through four customer-focused business segments: Communication Systems, Space and Intelligence Systems, Electronic Systems, and Critical Networks.

ENVIRONMENTAL SPECIFICATIONS

STANDARD	PARAMETER	METHODS & PROCEDURES
MIL-STD-810F	Vibration	514.5 PI, CAT 10
	Shock	516.5 PI
	Solar Radiation	505.4 PII
	Low Temperature	502.4 PI & II
	High Temperature	501.4 PI & II
	Temperature Shock	503.4
	Humidity	507.4 PI & II
	Low Pressure	500.4 PI & II

OPTION NUMBERS

XG-75P	MAH2-VC4PB
XG-25P	DP-CH4U
XG-15P	XR-VC4PB
P7300	MAH2-VC4PB
P5500	MAH2-VC4PB
P5400	MAH2-VC4PB
P5300	MAH2-VC4PB

REGULATORY SPECIFICATIONS

FCC Certification:	Meets FCC Part 15
Industry Canada:	ICES-003
Automotive Directive:	72/245/EEC – 95/54/EC

e11 10R-035194



Technical specifications are subject to change without notice. Product sales are subject to applicable U.S. export control laws.

FLORIDA | NEW YORK | VIRGINIA | BRAZIL | UNITED KINGDOM | UAE | SINGAPORE