



ADVANCED CONNECTIVITY IN EXTREME ENVIRONMENTS

KEY FEATURES

Optional cell modem for voice and data wherever cellular/LTE is available

Extends PTT coverage worldwide via Wi-Fi through Harris BeOn® application

Compact and lightweight, ruggedized to withstand extreme conditions

Built-in GPS, Bluetooth®, Active Noise Cancellation, and 4-position A-B-C-D switching is standard

XL-185P PORTABLE CONVERGED LTE LAND MOBILE RADIO

The Harris XL-185P is the industry's first and only single-band LTE LMR radio. Capable of operating on VHF, UHF, 700/800 or 900 MHz frequencies, this converged P25 portable merges robust LMR communications with voice and data over cellular, LTE and Wi-Fi®. The XL-185P is open standards-based, Verizon Certified and Band 14 ready, giving organizations a flexible upgrade path to emerging capabilities and networks as needs change.

Engineered for top performance in severe conditions, the XL-185P is an ideal, economical choice for public safety and utility workers. The portable features a ruggedized aluminum I-beam frame and meets MIL-STD-810G for durability, including Method 511.5 for explosive atmospheres and Method 504.1 for contamination by fluids, so it can be scrubbed with cleansers and biological sanitizers.

The XL-185P delivers industry-leading, loud audio powered by a 1.5 watt/4 watt max amplifier with woofer and tweeter speakers—and advanced

noise cancellation technologies suppressing audio feedback to provide clear communications through a wide range of conditions.

Compact and lightweight, the XL-185P fits naturally into users' hands, with controls shaped for fast, easy, gloved-hand operation. The color-coded display and easy-access A-B-C-D switching allows fast identification and selection of priority talk groups. First responders also avoid missing critical calls through the portable's ability to instantly recall and replay received audio.

SPECIFICATIONS FOR: XL-185P PORTABLE RADIO

GENERAL

Radio Models:	TFT LCD w/DTMF keypad, navigation cluster, soft keys	
Full Keypad	TFT LCD w/partial keypad, navigation cluster, soft keys	
Partial Keypad		
Dimensions w/Battery (H x W x D)	5.8 x 2.3 x 1.4 in (148.0 x 60.0 x 36.0 mm)	
Weight	w/Battery and Antenna	w/o Battery and Antenna
	16.2 oz (464 g)	10.4 oz (296 g)
Housing Colors	Midnight black, high-visibility yellow	
Interfaces:		
Front Display	320 x 178 pixels, 1.8 inch transfective LCD, 16-bit color with backlight	
Top Display	128 x 32 pixels, OLED 1.1 inch multi-color backlight, sunlight readable	
Keypad	Backlight, 3 soft keys, 5-way navigation key, full DTMF keypad	
Buttons	Large PTT button, on/off knob, volume knob, red emergency button, 16-position top-mounted rotary knob, 2-position concentric switch, 4-position toggle switch, 3 programmable side buttons	
Tx/Rx Indicator	Multi-colored LEDs	
Radio Programming	Firmware, personalities and feature set over Wi-Fi	
Transceiver	Supported Bands	Channel Capacity
	VHF, UHF, 700/800 MHz, 900 MHz, and LTE	12,500 (1,250 per mission plan)
Environmental:		
Relative Humidity	5% @ 140°F (+60°C), 95% @ 122°F (+50°C)	
Vibration	USDA LMR Standard, Section 2.15 and MIL-STD-810G, Test Method 514.6	
Drop Shock	1.5 meter drop to concrete (exceeds TIA-603-D)	
Immersion ¹	2 meters for 4 hours in accordance with MIL-STD-810G/IP68	
Operating Temperature²	-22°F to +140°F (-30°C to +60°C)	
Storage Temperature³	-40°F to +176°F (-40°C to +80°C)	
Altitude	Operational	In Transit
	15,000 feet (4,572 meters)	50,000 feet (15,240 meters)
Electrical Input Voltage	7.5 VDC (nominal)	
GPS/GNSS Specifications:		
Channels	52	
Tracking Sensitivity (dBm)	-166 (GPS), -163 (GLONASS)	
Acquisition Sensitivity (dBm)	-146 (GPS)	
Cold Start w/-130 dBm input	<35 seconds	
Hot Start w/-130 dBm input	<1 second	
Safety:		
Hazardous Location Options		
RoHS Compliant		

¹ Optional feature

² Extreme low temperatures adversely affect battery life and audio power/ distortion

³ Store batteries at +25°C ± 5°C

LMR TRANSMITTER

Frequency Bands	VHF	UHF	700/800 MHz	900 MHz
Frequency Ranges (MHz)				
Option 1 (US)	136-174	378-522	768-776, 798-806, 806-816, 851-861	896-902, 935-944
Option 2 (International)	136-174	378-522	763-776, 793-806, 806-825, 851-870	896-902, 935-944
Rated RF Power/Talkaround (W)	1-6	1-5	0.5-3	0.5-3.5
Frequency Stability (-30 to +60°C)	±1.0 ppm	±1.0ppm	±1.0 ppm	±1.0 ppm
Modulation Limiting (kHz)	2.5, 4, 5 (FM)	2.5, 4, 5 (FM)	2.5, 4, 5 (FM)	2.5, 4, 5 (FM)
Audio Response (dB)	+1/-3	+1/-3	+1/-3	+1/-3
Spurious and Harmonics (dBc)	-80 (FCC Part 90)	-80 (FCC Part 90)	-80 (FCC Part 90)	-80 (FCC Part 90)
FM Hum and Noise Companion Receiver (dB):				
@ 25 kHz	70	60	55	55
@ 12.5 kHz	47	47	45	45
Audio Distortion (%)	<1.25	<1.25	<1.25	<1.25
Project 25 Modulation Fidelity (%)	1.0	1.0	1.0	1.0
Project 25 Adjacent Channel Power (dBc)	>71	>71	>71	>70

SPECIFICATIONS FOR: XL-185P PORTABLE RADIO

REGULATORY DATA							
Frequency Range	RF Output	Frequency Stability	FCC Type Acceptance No.	Applicable FCC Rules	Industry Canada Certification No.	Applicable Industry Canada Rules	NTIA Cert. No.
136 - 174 MHz	6 W	±1.0 ppm	OWDTR-0150-E	22, 74, 80, 90	3636B-0150	RSS-119	SPS-217 49/1
378 - 522 MHz	5 W	±1.0 ppm	OWDTR-0149-E	22, 74, 80, 91	3636B-0149	RSS-119	SPS-217 49/1
768 - 776 MHz	3 W	±1.0 ppm	OWDTR-0147-E & OWDTR-0148-E	90	3636B-0147	RSS-119	
798 - 806 MHz	3 W	±1.0 ppm	OWDTR-0147-E & OWDTR-0148-E	90	3636B-0147	RSS-119	
806 - 816 MHz	3 W	±1.0 ppm	OWDTR-0147-E	90	3636B-0147	RSS-119	
806 - 825 MHz	3 W	±1.0 ppm	OWDTR-0148-E	90	3636B-0148	RSS-119	
851 - 861 MHz	3 W	±1.0 ppm	OWDTR-0147-E	90	3636B-0147	RSS-119	
851 - 869 MHz	3 W	±1.0 ppm	OWDTR-0148-E	90	3636B-0148	RSS-119	
896 - 901 MHz	3w	±1.0 ppm	OWDTR-0143-E	90, 24D, 101	3636B-0143	RSS-119	
901 - 902 MHz	3w	±1.0 ppm	OWDTR-0143-E	90, 24D, 101	3636B-0143	RSS-119	
940 - 941 MHz	3w	±1.0 ppm	OWDTR-0143-E	90, 24D, 101	3636B-0143	RSS-119	
935 - 940 MHz	3w	±1.0 ppm	OWDTR-0143-E	90, 24D, 101	3636B-0143	RSS-119	
941 - 944 MHz	3w	±1.0 ppm	OWDTR-0143-E	90, 24D, 101	3636B-0143	RSS-119	
2402 - 2460 MHz	VHF single band	0.2 W	N/A	OWDTR-0150-E	15	3636B-0150	RSS-119
	UHF single band	0.2 W	N/A	OWDTR-0149-E	15	3636B-0149	RSS-119
	RB single band	0.2 W	N/A	OWDTR-0147-E	15	3636B-0147	RSS-119
	NRB single band	0.2 W	N/A	OWDTR-0148-E	15	3636B-0148	RSS-119
5180 - 5825 MHz	VHF single band	.01 W	N/A	OWDTR-0150-E	15	3636B-0150	RSS-119
	UHF single band	.01 W	N/A	OWDTR-0149-E	15	3636B-0149	RSS-119
	RB single band	.01 W	N/A	OWDTR-0147-E	15	3636B-0147	RSS-119
	NRB single band	.01 W	N/A	OWDTR-0148-E	15	3636B-0148	RSS-119

LMR RECEIVER				
Frequency Bands	VHF	UHF	700/800 MHz	900 MHz
Frequency Ranges (MHz):				
Option 1 (US)	136-174	378-522	768-776, 851-861	935-944
Option 2 (International)	136-174	378-522	763-776, 851-870	935-944
Channel Spacing (kHz)	25 (wideband), 12.5 (narrowband), 6.25 equiv (TDMA P25 Phase 2)		25 (wideband), 12.5 (narrowband), 6.25 equiv (TDMA P25 Phase 2)	
Frequency Stability (-30 to +60°C)	±1.0 ppm	±1.0 ppm	±1.0 ppm	±1.0 ppm
Sensitivity (dBm):				
@ 12 dB SINAD	-122	-121	-121 (700 MHz) -120 (800 MHz)	-120 (900 MHz)
Project 25 Reference Sensitivity (dBm):				
@ 5% BER	-122	-121	-120.5	-120.5
Analog Selectivity (dB):				
@ 25 kHz	77	77	74	74
@ 12.5 kHz	71	70	64	64
Project 25 Adjacent Channel Rejection (dB)	66.2	62.2	62	62
Offset Channel Selectivity (dB):				
@ NPSPAC	NA	NA	30	30
Intermodulation (dB)	80	81	77	77
Spurious and Image Rejection (dB)	90	87	80	80
FM Hum and Noise (dB):				
@ 25 kHz	-60	-60	-55	-55
@ 12.5 kHz	-55	-53	-50	-50
Audio Output - Rated/Max (mW)	1500/4000	1500/4000	1500/4000	1500/4000
Audio Distortion @ Rated Power (%)	1.1	1.1	1.1	1.1

BROADBAND	
LTE Protocol	3GPP Release 9, Power Class 3 UE with Rx diversity
Public Safety Broadband	Band 14, 788-798 MHz Tx, 758-768 MHz Rx, 5 or 10 MHz BW
Commercial Broadband	Band 13, 777-787 MHz Tx, 746-756 MHz Rx, 5 or 10 MHz BW
Commercial Broadband	Band 4, 1710-1755 MHz Tx, 2110-2155 MHz Rx, 5, 10, 15, or 20 MHz BW
Wi-Fi	802.11 b/g/n 2.4 GHz and 5 GHz; supports 24 preconfigured and 8 user configured networks
Bluetooth	Bluetooth 4.0 (128-bit encryption)

SPECIFICATIONS FOR: XL-185P PORTABLE RADIO

DIGITAL OPERATION

Protocol	ProVoice™	P25
Vocoding Method	AMBE +2™ enhanced full rate	AMBE +2 enhanced full rate and enhanced half rate
Signaling Rate (kbps)	9.6	9.6
Modulation	GFSK	Phase 1 Tx: C4FM, Rx: C4FM and WCQPSK
Harris Failsoft operation	Switch to site trunking mode (for Harris infrastructure) or P25 conventional	

ENCRYPTION

Encryption Algorithms	Voice Encryption: Single-key AES/DES, Multiple-key AES/DES, DES-OFB, Encryption Lite (ARC4), 256-bit AES P25, 64-bit DES Control Channel Encryption: 128-bit AES (LLA)	
Encryption Keys per Radio	Capable of storing 128 keys (128 AES, 64 DES)	
Keying	Harris Key Loader, Over-the-Air Rekeying (OTAR), Motorola KVL 3000+/4000	
Standards	FIPS 140-2, FIPS 197	

BATTERIES

Type	Dimensions (H x W x D)	Weight	Capacity (mAh)
Li-Ion	3.0 x 2.3 x 0.9 in	4.8 oz (136 g)	3100

Technical specifications are subject to change without notice. Product sales are subject to applicable U.S. export control laws.

ACCESSORIES

Headsets

The XL-185P can be used with a wide variety of headsets and covert audio accessories to provide a complete user-gear solution for the industrial, public safety, utility and transportation markets. Heavy-duty and lightweight headsets are available with in-ear or over-the-ear hearing protection, flexible boom microphones with noise-reduction technology, and standard or remote PTTs. In addition, the XL-185P can be used with Bone Conducting Skull Headsets and Throat Microphone/Headset Kits. Covert audio kits are available in black or beige, 2-wire or 3-wire configurations with ear-piece, microphone and PTT.



3-Wire Mini-Lapel Microphone



Tactical Headset

Carrying Cases

Harris offers a versatile line of carrying cases for the XL-185P single-band radio. Options include a standard belt clip and premium belt loop, providing the user a low-profile, integrated carrying option. In addition, a premium leather holster is available for attaching to a belt or wearing with the premium leather shoulder strap.



Belt Clip



Leather Carrying Case

Chargers

Harris offers a variety of chargers for the XL-185P including Single-Bay, Multi-Bay and a Vehicular Charger for in-car charging. The chargers are designed to quickly and safely charge battery packs in approximately 1 to 4 hours.



Single-Bay Charger



Multi-Bay Charger*



Vehicular Charger*

Additional Accessories Available

Bluetooth speaker microphones, Bluetooth covert earpieces, standard speaker microphones, Lithium Ion battery, PC programming software and cables, other subminiature surveillance accessories, and antennas.

Technical specifications are subject to change without notice. Product sales are subject to applicable U.S. export control laws.

*Accessories unavailable in Brazil

About Harris Corporation

Harris Corporation is a leading technology innovator, solving customers' toughest mission-critical challenges by providing solutions that connect, inform and protect. Harris supports government and commercial customers around the world.

Learn more at harris.com

FLORIDA | NEW YORK | VIRGINIA | BRAZIL | UNITED KINGDOM | UAE | SINGAPORE

Non-Export Controlled Information

Harris is a registered trademark of Harris Corporation. Trademarks and trade names are the property of their respective companies.

© 2018 Harris Corporation. Available on request. 03/18 DS1895C

HARRIS® TECHNOLOGY TO CONNECT,
INFORM AND PROTECT™